

For tough jobs ...

Sweeper for excavators BK 750 / 950

NEW

- ▶ For tracked and mobile excavators from 1.7 t up to 25 t
- ▶ 750 mm or 950 mm brush diameter depending on working width
- ▶ Internal hydraulic motor - with BK 950
Two internal drive motors
- ▶ Standard overrun protection with pressure relief valve
- ▶ Complete with integrated parking device
- ▶ Optionally with spring-loaded pendulum for optimum ground adjustment
- ▶ With optional slewing ring for 90° rotation of the machine (mechanical or hydraulic)



Profile ADLER excavator sweeper BK 750 / 950

Rolling chippings, rubble, coarse dirt, snow - the ADLER sweeper for tough applications

The ADLER excavator sweeper helps you to sweep your building sites, whether in road construction, pipeline laying, pavement sweeping or surface cleaning. You can quickly adapt and hydraulically connect your BK 750 / 950 excavator sweeper using the quick-change attachment on your excavator- and off you go!

The hydraulic system of your excavator drives the internal hydraulic motor and thus the brush shaft. An overrun protection system fitted as standard protects the hydraulic motor from pressure peaks and ensures a long service life for the motor. You can use your tracked and mobile excavators from 1.7 t up to 25 t.

With a brush diameter of 750 mm or 950 mm, the powerful excavator sweepers also remove heavy soiling quickly and effectively. As an option, a dirt scraper can also be used to scrape even caked-on dirt from the road surface. The ADLER BK 750 / 950 excavator sweeper is the ideal addition for fast cleaning operations on your site.


Accessories:

- ▶ Turntable for 90° rotation of the machine (mechanical or hydraulic)
- ▶ Spring-loaded pendulum for optimum adaptation to the ground
- ▶ Flow control valve for limiting the oil volume to the permissible flow rate

ADLER-excavator sweeper BK 750 / 950		90	120	150	150	180	210	240
Working width	cm	90	120	150		180	210	240
Overall width	cm	114	143	173	181	210	240	270
Brush diameter	mm	750	750	750	950	950	950	950
Required hydraulic pressure and volume		160 bar / > 35 l/min			160 bar / > 60 l/min			
Weight	kg	195	216	237	453	489	525	566



Brush diameter: 750 mm (up to 1,500 mm working width) or 950 mm (from 1,500 mm to 2,400 mm working width)



Slewing ring to turn the machine 90° – hydraulically or mechanically



Spring-loaded pendulum adapts perfectly to the ground



ADLER BK 750 / 950 always with integrated parking device



Powerful hydraulic motors with motor-preserving overrun protection



Insert for vertical use with power tilt function on the excavator